

# (12) UK Patent Application (19) GB (11) 2 359 157 (13) A

(43) Date of A Publication 15.08.2001

(21) Application No 0022534.2

(22) Date of Filing 14.09.2000

(30) Priority Data

(31) 09409598

(32) 30.09.1999

(33) US

(71) Applicant(s)

International Business Machines Corporation  
(Incorporated in USA - New York)  
Armonk, New York 10504, United States of America

(72) Inventor(s)

Christopher Shane Claussen  
Michael Haden Conner  
Matthew Dale McClain  
Benjamin Charles Zumbrunnen

(74) Agent and/or Address for Service

IBM United Kingdom Limited  
Intellectual Property Department, Hursley Park,  
WINCHESTER, Hampshire, SO21 2JN,  
United Kingdom

(51) INT CL<sup>7</sup>

G06F 17/30 9/45 17/21

(52) UK CL (Edition S )

G4A APL AUB

(56) Documents Cited

WO 00/45304 A1  
[http://www.chesco.com/~randzman/CFDOCS/moredocs/adv\\_cf\\_devel.pdf](http://www.chesco.com/~randzman/CFDOCS/moredocs/adv_cf_devel.pdf), Adv ColdFusion Development, 07/9/00  
<http://www.redbooks.ibm.com/pubs/pdfs/redbooks/sg245479.pdf> The XML Files..., 27/03/2000  
<http://java.sun.com/products/jsp/techinfo.html>, JavaServer pages specification 1.0, 27/9/1999  
[http://www.cs.nyu.edu/others/research/mu\\_spin/muspin99.pdf](http://www.cs.nyu.edu/others/research/mu_spin/muspin99.pdf) MU-SPIN 9th Ann. Users Conf. 27/09/1999  
<http://zdnet.com/filters/printerfriendly/0,6061,409493-2,00.html>, Lutris' server divides... 11/07/1999

(58) Field of Search

UK CL (Edition S ) G4A APL AUB  
INT CL<sup>7</sup> G06F 9/30 9/44 9/45 17/21 17/30  
Online: WPI, EPODOC, PAJ, COMPUTER, INSPEC, IEL and selected internet sites

(54) Abstract Title

Extensible Markup Language (XML) server pages having custom Document Object Model (DOM) tags

(57) A method for serving a web page uses eXtensible Markup Language (XML) server pages. The first time a web page is accessed, a given flat file is parsed into an XML Document Object Model (DOM) 204, 206, and required tag libraries are loaded. The DOM tree is then traversed, preferably in a depth first, inside-out manner to locate custom tags. Upon locating a custom tag a handler is invoked that converts the custom tag into a given representation whereby if the tag is registered as a Java object, the object is loaded. A process method is then called on the object, passing the custom tags' tree node. The Java object then examines the custom tag and replaces it with an object, e.g. script code. Alternatively, if the tag is registered as an XSL stylesheet, the stylesheet is loaded and passed, together with the DOM, to an XSL processor. The processor applies the template to the custom tag and replaces it with given script code. Once all custom tags are reduced to HTML and script code, the DOM is compiled into a Java servlet 210 to service the client request. Furthermore, the custom tag(s) and data identifying their associated handler(s) may be registered prior to processing the flat file.




FIG. 2

GB 2 359 157 A




FIG. 1





FIG. 2






FIG. 4





FIG. 5

FIG. 6






FIG. 7




FIG. 8





FIG. 9

FIG. 10






FIG. 11



EXTENSIBLE MARKUP LANGUAGE (XML) SERVER PAGES  
HAVING CUSTOM DOCUMENT OBJECT MODEL (DOM) TAGS

The present invention relates generally to Internet publishing technologies and, in particular, to techniques for dynamically serving web page content.

A Hypertext Markup Language (HTML) file uses a limited set of tags to convey basic information about the structure of a web document, e.g., whether given text is a heading or a paragraph. With HTML, the style and logic of the document are hardcoded. HTML does not provide tags that define the meaning of the page element. To address this limitation, web content is now being authored in eXtensible Markup Language (XML), which provides a way for an author to create a custom markup language to suit a particular kind of document. In XML, each document is an object, and each element of the document is an object. The logical structure of the document typically is specified in a Document Type Definition (DTD). A DTD may be used by the author to define a grammar for a set of tags for the document so that a given application may validate the proper use of the tags. A DTD comprises a set of elements and their attributes, as well as a specification of the relationship of each element to other elements. Once an element is defined, it may then be associated with a stylesheet, a script, HTML code or the like. Thus, with XML, an author may define his or her own tags and attributes to identify structural elements of a document, which may then be validated automatically. An XML document's internal data structure representation is a Document Object Model (DOM). The DOM makes it possible to address a given XML page element as a programmable object. It is basically a tree of all the nodes in an XML file.

Page serving technologies are evolving at a rapid pace. Since 1997, three new major technologies have attempted to supplement, if not replace, dynamically generated HTML, i.e. database or CGI scripts used to generate a web page on the fly. These technologies are Microsoft's active server page (ASP)<sup>(RTM)</sup>, Sun Microsystems's Java server<sup>(RTM)</sup> page (JSP), and the Extensible Style Sheet Language (XSL/XSLT) being promoted by the World Wide Web Consortium (W3C)<sup>(RTM)</sup>. They provide for the generation and serving of dynamic web page content by enabling a page creator to write HTML and then to embed pure programming logic inside the page markup. Microsoft's ASP and Sun's JSP are very similar in that they both are essentially web templates that enable given code (e.g., code written in Java) to be embedded in static

HTML to be served in response to a client browser request. In an illustrative example, a server (and, in particular, a Java<sup>(RTM)</sup> runtime servlet) responds to a client .jsp request as follows: the servlet retrieves a flat file corresponding to the requested page, translates that file into a Java servlet, compiles the servlet, class loads the servlet, and then invokes the servlet to cause given (e.g., customized) web content to be returned to the requesting browser. XSL/XSLT, to the contrary, is rooted in formatting and manipulating XML. XSLT, in particular, provides extensible mechanisms for defining templates to manipulate XML of any custom DTD.

The existing techniques for serving dynamic content have various limitations. Conventional server-side scripting on a web page can be complicated and, therefore, such scripting is usually difficult to maintain and evolve. Further, with existing technologies, typically only a single scripting language is allowed on a web page. This limitation is acceptable, so long as only one author is responsible for editing the page, or if all of the responsible authors know and use the same scripting language and the language of choice is supported by the web server. Microsoft's ASP technology supports multiple scripting languages, but only one language may be used on a page. Moreover, multiple languages cannot be embedded in one another, and their order of execution is undefined. Further, page-serving technologies such as ASP and JSP are not XML-compliant, and neither ASP nor JSP provides an extension mechanism to allow authors to add custom tags.

It is also known in the art to provide a web page author with a library of preexisting custom tags. An illustrative product of this type is Cold Fusion<sup>(RTM)</sup>, which is HTML-centric. This product, however, does not afford the author the ability to create custom tags. Macromedia's Dreamweaver<sup>(RTM)</sup> product has a tag construction mechanism, but this product does not allow for the embedding of custom tags, nor does it allow the document to be reorganized by the tags. It also keeps the script code on the page. In particular, the script is hidden from the user, but it is still present on the page, and it may be viewed and/or edited from within another editor. However, the modifications made in another tool are not maintained. Microsoft provides a similar technology, called design-time control (DTC)<sup>(RTM)</sup>, that hides code from the user but still maintains the code on the page. DTC is not XML-compliant and it does not allow DTCs to be embedded within one another. Nor does the DTC mechanism allow the document to be reorganized. In addition, the DTC syntax is quite cumbersome for the page author. Moreover, while other DTC-aware tools will hide the script code

correctly, basic text-editors can still edit the code, and the changes made will not be importable back into the DTC-aware tools. DTC also does not provide access to the Document Object Model. Other products or technologies that have custom tag extensions include HeiTML and Meta-HTML. Essentially, these are tag macro definition languages for HTML. Such languages, however, are not XML compliant.

There remains a need in the art to provide new techniques for publishing Internet content that can fully leverage the manipulation and template mechanism of XSLT with the scripting capability of the JSP/ASP model. The present invention addresses this need.

According to an embodiment of the present invention, a web page author may define a custom DOM (Document Object Model) tag in a web page that, at page-translation time, is converted into script code (e.g., by a Java object or an XSL stylesheet). This script code is then compiled into Java code, and then into a Java servlet, yielding excellent performance in servicing a client's request for the page. Because the custom tag serves as a marker for a tag handler that manipulates the document, the page is kept clean and easy to maintain. The script code is kept separate and, therefore, need only be debugged once.

In a preferred embodiment, custom tags are registered in an XML tag library file. This file preferably includes the name of the custom tag as well as a Java object name or a URL naming an XSL stylesheet. The first time the page is accessed, the page handling engine of the present invention parses it into an XML Document Object Model (DOM), and all the required tag libraries are loaded. The engine then traverses the DOM tree, preferably in a depth-first inside out manner, looking for registered custom tags. Upon finding one, if the tag is registered as a Java object, a bean is loaded, and a "process" method is then called, passing the custom tag's tree node. The Java object has access to the entire DOM, and it may modify the DOM however it deems necessary. Thus, for example, the Java object examines the custom tag and replaces it with other custom tags, script code, or HTML. Once processing is complete, the DOM is reexamined to identify any new tag library directives and new custom tags. If necessary, appropriate tag bean handlers are then invoked recursively according to a custom tag search algorithm.

According to a preferred embodiment, a method for processing a document object model (DOM) tree including a set of custom tags begins by

verifying a DOM data representation (e.g., a tree) against a Document Type Definition (DTD). Thereafter, the DOM tree is examined in a given manner, preferably, in a depth first, inside-out manner. For each custom tag in the DOM tree, the routine performs a number of substeps: retrieving a left-most leaf node in the tree that is the custom tag, invoking a handler for the left-most leaf node, e.g., to replace the custom tag with given script code, and registering, with a tag registry, any new tag libraries that are generated as a result of invoking the handler. After all custom tags in the DOM tree have processed up the tree, the tree is preferably collapsed into a fewest possible number of method blocks.

An embodiment of the invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is a simplified illustration of a client-server environment in which the present invention may be implemented;

Figure 2 is a high level flowchart illustrating a servlet generation routine;

Figure 3 is a flowchart illustrating how one preferred technique for preprocessing a flat file into XML compliant code;

Figure 4 is a flowchart illustrating a preferred algorithm for processing custom tags;

Figure 5 is a flowchart illustrating a custom DOM tag XSL handler routine for an XSL style sheet;

Figure 6 is a flowchart illustrating a custom DOM tag Java handler routine for a Java object;

Figure 7 is a flowchart illustrating the operation of a DOM In, Text Out tagbean;

Figure 8 is a flowchart illustrating the operation of a Text In, Text Out Text tagbean;

Figure 9 is a flowchart illustrating a routine for supporting multiple scripting languages in a single page;

Figure 10 is a flowchart illustrating a routine for collapsing a DOM tree into a fewest number of method calls; and

Figure 11 is a flowchart illustrating a routine for verifying the context of related XML tag elements in a DOM tree.

The present embodiment is a page handling framework and runtime engine operative on a server in a computer network such as the Internet. As is well-known, in the Internet paradigm as illustrated in Figure 1, a client machine, such as machine 10, may use an application, such as a web browser 12, to access a server 14 via a computer network 16. Network 16

typically includes other servers (not shown) for control of domain name resolution, routing and other control functions. A representative server 14 is a computer or workstation having at least one processor 18, system memory (e.g., RAM) 20, disk or other permanent storage 22, I/O devices 24a-n, an operating system 26, a server program 28, and an application programming interface (API) 30 that provides extensions to enable application developers to extend and/or customize the core functionality thereof through software programs including plug-ins, CGI programs, Java servlets, and the like. One such software program is an inventive page handling mechanism 32, which processes an HTTP page request and generates a response by feeding data into an output stream as will be described. In an illustrative embodiment, the page handling mechanism is implemented in Java and is executable in a Java Virtual Machine (JVM) by a processor in a known manner. Alternatively, the program may be written in whole or in part in native code. The inventive functionality, of course, may be part of the integral web server program.

A representative server machine is an IBM Netfinity<sup>(RM)</sup> platform running the Unix<sup>(RM)</sup> operating system and a server program such as IBM WebSphere<sup>(RM)</sup> Version 2.0. Of course, any other computer hardware or software may be used.

A representative client is a personal computer, notebook computer, Internet appliance or pervasive computing device (e.g., a PDA or palm computer) that is Pentium<sup>(RM)</sup>, PowerPC<sup>(RM)</sup> or RISC-based. The client includes an operating system such as Microsoft Windows<sup>(RM)</sup>, Microsoft Windows CE or PalmOS<sup>(RM)</sup>. A typical client includes a suite of Internet tools including a Web browser, such as Netscape Navigator<sup>(RM)</sup> or Microsoft Internet Explorer, that has a Java Virtual Machine (JVM) and support for application plug-ins or helper applications. Communications between the client and the server typically conform to the Hypertext Transfer Protocol (Version 1.0 or higher), and such communications may be made over a secure connection.

The flowcharts of Figures 2-11 illustrate the inventive functionality of the page handling mechanism.

### Servlet Generation

Figure 2 illustrates how a flat web page file is processed to generate a servlet. The routine begins at step 200 by retrieving a flat file from the server's database. At step 202, a test is made to determine whether a timestamp for the flat file is later than a timestamp for the

class load for the file. If the outcome of the test at step 202 is negative, the file has already been processed. Control then branches to step 214, where the file is invoked as a runtime operation. If the outcome of the test at step 202 is positive, the routine continues at step 204 to preprocess the flat file into XML compliant code and, at step 206, to transform the XML into a Document Object Model (DOM) data representation. The Document Object Model is a platform- and language-neutral interface that allows programs and scripts to dynamically access and update the content, structure and style of documents. In particular, the Document Object Model provides a standard set of objects for representing HTML and XML documents, a standard model of how these objects can be combined, and a standard interface for accessing and manipulating them. The Document Object Model (DOM) Level 1 Specification is available from the World Wide Web Consortium.

Step 204 is illustrated in more detail in Figure 3. Preferably, steps 204-206 are accomplished concurrently using an XML parser, such as the IBM WebSphere XML4J parser. The routine then continues at step 208. At this step, the DOM along with its namespaces are interpreted to produce a Java object, such as a servlet. This process is illustrated in more detail in Figure 4. Thus, in particular, steps 204, 206 and 208, the present embodiment generates a page template via DOM translation of the flat file. At step 210, the servlet is compiled. The routine then continues at step 212 to class load the servlet. Control then continues at step 214, which has been previously described.

Steps 204-212 preferably occur at page translation time. Page translation typically occurs the first time the page (namely, the request for the flat file) is accessed or hit. Step 214 is executed to serve the requested page in response to the originating HTTP client request. In particular, the servlet is invoked with standard HttpRequest and HttpResponse objects, and it generates a response by feeding data into an output stream. The data is provided to the client browser for rendering in the usual manner.

The above-described embodiment provides several advantages over the prior art. As noted above, the routine illustrated in Figure 2 preferably occurs at page translation time, which provides significant processing efficiencies. Moreover, it enables custom tags to be embedded within one another, which has not been available in the known art. It provides the

further advantage of enabling the implementation of translation semantics using XSL stylesheets, which is also new to the art.

### File Preparing

Figure 3 illustrates a preferred technique preparing a flat file into XML compliant code. This was step 204 in Figure 2.

The routine begins at step 302 by passing the flat file to the preprocessor. At step 306, the input stream comprising the flat file is broken into tokens. The routine then performs a test at step 308 to determine whether the stream has any more tokens to process. If so, the routine continues at step 310 to test whether the token is a known JSP (or ASP) symbol. If the outcome of the test at step 310 is positive, the routine branches to step 312 to turn the JSP symbol into an XML tag. If the outcome of the test at step 310 is negative, the routine branches to step 314 to identify any text that violates XML constraints. Following either step 312 or step 314, the routine continues at step 316 to place the token in an output stream holder. Control then returns to step 308 to process additional tokens. If the outcome of step 308 is negative, however, the routine branches to step 318 to verify that the "jsp:root" tag exists in the stream. At step 320, the parser turns tag libraries into "jsp:root" namespace attributes. The routine then continues at step 322 by constructing the output stream. This completes the preparing routine.

### Processing a DOM with Custom Tags

A preferred algorithm for processing a DOM with custom tags is illustrated in Figure 4. Preliminary processing is provided by steps 402-412. These steps may be omitted. In particular, the routine begins at step 402 by verifying the DOM, for example, with a JSP DTD. At step 404, the routine adds servlet generation variables to the root element of the DOM for later handling. The routine then continues at step 406 to gather all jsp:directive.page tags to ensure a consistent state. At step 408, the jsp tag libraries (which provide support for JSP 1.0 mechanisms) are registered with the root element. Thus, for example, custom tags are registered through an XML <taglib = "tag-library.xml"> tag, according to the JSP 1.0 specification.

By way of brief background, where a plurality of custom tags exist, it is desired to provide a cataloging and registration mechanism to organize the tags and to prevent naming collisions. According to the present embodiment, a tag library, or "taglib," is used for this purpose.

As will be described below, the tag library is preferably specified by a URI and comprises a page, preferably XML, identifying the tag namespace and listing the tags recognized in the namespace as well as the directives on how to load the appropriate tag handlers. Thus, in a representative embodiment, in the tag-library-xml file, the name of the custom tag is listed, as well as a Java object name, or a URL identifying an XSL stylesheet.

The following is an example of a custom tag library:

In the JSP context:

```
<jsp:root xmlns:sample="/xsp/sample/sample-taglib.xml">
</jsp:root>
```

Here, a namespace "sample" is defined by the relative URL of "/xsp/sample/sample-taglib.xml".

The content at the URL would look as follows:

```
<?xml version="1.0"?>
<taglib>
  <tag name="currentTime"
        class="xsp.sample.CurrentTimeTagBean"
        dtd="currentTime.dtd"/>
  <tag name="currentTimeXSL"
        styleSheet="http://localhost/xsp/sample/currentTimeCustomTag.xsl"
        dtd="currentTime.dtd"/>
</taglib>
```

This registers a Java TagBean to handle sample:currentTime tags and registers the currentTimeCustomTag.xsl as an XSL handler for sample:curentTimeXSL. As a bonus, both register currentTime.dtd to verify the correctness of the sample:currentTime and sample:currentTimeXSL tags before the formatting of those tags occurs.

Returning now to Figure 4, the routine then continues at step 410. In particular, any additional tag libraries are gathered and registered with a main tag handler. A tag handler is a process that is used to hand-off execution (of a custom tag in the DOM) to some other process, e.g., a Java object (through a custom tag interface), or via an XSL stylesheet. The routine then continues at step 412 by inserting a



...jspServiceMethodDefinition as the last child of the jsp:root element. The methodDefinition preferably has the content of most of the servlet code. As will be described in more detail below, the jsp:block element is appended to the methodDefinition to begin the servlet's definition as a Java code block by default or with as the value of the jsp page directive attribute (if it is specified).

The main processing of the routine begins at step 416. At this step, a test is made to determine whether the DOM tree has any custom tags that have not been processed. If so, the routine branches to step 418 to locate preferably the left-most leaf node of the tree that satisfies its requirements as a custom tag. The routine then continues at step 420 to invoke an appropriate tag handler (e.g., a Java object, the XSL stylesheet, or the like). Two variations of step 420 are illustrated in the flowcharts of Figures 5-6. As will be seen, the appropriate tag handler is given a current tag element and is expected to process it. Typically, a new DOM is returned from the tag handler and is then processed for new tag libraries. At step 422, the new tag libraries are registered in the tag library registry. The routine then continues at step 424 to gather all new jsp:directive tags. The routine then returns to step 416.

This loop continues until all custom tags have been processed in a like manner. When the outcome of the test at step 416 is negative, the routine branches to step 426 to collapse the resulting DOM tree into as few as possible method blocks. This operation is illustrated in Figure 10. The routine then continues at step 428 to generate the servlet by interpreting scriptlet, expression, declaration and methodDefinitions. Thus, for example, at step 428, the routine interprets the DOM by replacing "jsp:scriptlets" with inlined code, by replacing "jsp.expressions" with prints, by replacing "jsp:declarations" with variables and method definitions, by replacing "xsp:methodCalls" with method calls, and by replacing "xsp:methodDefinitions" with method definitions. As described in Figure 2, the resulting servlet is then compiled and class loaded to be ready for use by the runtime code.

#### Custom Tag Definition

Preferably, the DOM tree identifies custom tags as follows. As noted above, the JSP 1.0 specification included a tag library mechanism that defines how to plug in a tag. The specification, however, left the details of the taglib mechanism completely open, with the exception that a url must be used to specify the location of the taglib. According to the

present embodiment, this abstract concept has been unified with an XML namespace and mapped into an XML file. In an illustrative embodiment, the Document Type Definition (DTD) for a taglib is:

```

<!ELEMENT taglib (tag)*>
5 <!ELEMENT tag EMPTY>
  <!-- Note: either class or styleSheet must exist (but preferably not both)
  -->
  <!ATTLIST tag
        name          CDATA #REQUIRED
10        class        CDATA #IMPLIED
        styleSheet    CDATA #IMPLIED
        dtd           CDATA #IMPLIED>

```

This data structure defines that a tag library is composed of zero or more tags. Each tag is defined with a name and optional attributes class, styleSheet, and dtd. A tag must have either a class or styleSheet attribute (but preferably not both) to specify a correct tag handler. The value of name is used to identify what tags it handles. If a tag's name is "scriptlet" and its taglib prefix is "jsp", then this rule handles any tag named "jsp:scriptlet". The class and styleSheet attribute dictate which of the two mechanisms are used to handle a custom tag. If the rule specifies a class, then a Java object, e.g., an object satisfying a custom tag interface, is used to process the tag. If the rule specifies a styleSheet, then an XSLT styleSheet is used to process the tree. The optional dtd parameter is used to verify the contents of the custom tag, for example, whether the tag has the proper attributes.

As noted above, Figures 5-6 illustrate the preferred tag handling routines. As described, there are two types of tag handling: tags handled by XSLT (Figure 5) and tags handled by Java code (Figure 6). Each of these handlers will now be described in more detail.

#### XSL Custom Tag Handler

The XSL tag handler routine begins at step 502 by receiving the DOM element as input. At step 504, the tag handler then finds the appropriate stylesheet for the element as supplied by the taglib rules. The routine then continues at step 506 with the tag handler obtaining the element's parent document. At step 508, the routine invokes a stylesheet processor on the document and stylesheet. Finally, at step 510, the tag handler returns the new document to complete the translation.

Java Object Custom Tag Handler

Figure 6 illustrates a preferred operation of the custom DOM tag Java object handler. By way of brief background, as used herein, a "tagbean" is a Java object that implements a TagBean interface. Preferably, the interface is as follows:

```

5 public interface TagBean
    {
        public void
10     process(Element element);
    }

```

The TagBean interface defines a process method that takes an element in from the DOM tree and performs some function against that element. The context of the entire DOM tree is available to the process method for manipulation through the DOM APIs.

The routine begins at step 602 with the Java tag handler receiving the DOM element as input. At step 604, the handler then obtains the appropriate tagbean for the element as supplied by the taglib rules. A number of tagbean routines are illustrated in Figures 7-9 and will be described in more detailed below. At step 606, the handler extracts an attributeList from the element. The routine then performs a test at step 608 to determine whether there are any unprocessed attributes. If so, the routine branches to step 610 to determine whether the attribute maps to a setter property on the tagbean. If the outcome of the test at step 610 is negative, control returns to step 608. If, however, the outcome of the test at step 610 is positive, the routine continues at step 612 to set the value of the attribute on the tagbean. Control then continues at step 614 to remove the attribute from the attributeList. Processing then continues back at step 608.

Thus, for each attribute in the attributeList, the handler checks for a corresponding setter property on the tagbean. If a corresponding setter property exists, the value of the attribute is set on the tagbean and the attribute is removed from the attribute list. When the outcome of the test at step 608 indicates that all attributes have been checked against the tagbean, routine branches to step 616. At this step, the tagbean's process method is called given the DOM element so that it can manipulate the tree in whatever manner it deems fit. When tagbean.process() is complete, the new document is returned from the tag handler at step 618. This completes the processing.

Figures 7-9 illustrate tagbeans that are useful in the present embodiment.

#### DOM In, Text Out Tagbean

Figure 7 illustrates a simple DOM in, Text out macro that has the following class:

```
public abstract class SimpleTagBean implements TagBean
{
    public abstract String
    translateElement(Element element);

    public final void
    process(Element element);
}
```

SimpleTagBean is a class created to simplify the task of writing a tagbean. Using this class, the developer merely has to implement the translateElement method, which takes in a DOM element and returns the corresponding text macro expansion. In particular, the routine reads the DOM tree (e.g., using the DOM APIs), produces an XML block (typically a scriplet), and uses the XML block to replace the current element in the tree. This is advantageous to the writer of the tagbean because, he or she does not need to know how to create new nodes and to populate them with values. All the writer has to do is create an XML expanded form of the element passed in. While this approach requires increased execution time at translation, translation only happens once every time the page changes; thus, the technique has little impact on server performance.

The SimpleTagBean class works as demonstrated in the flowchart of Figure 7. The routine begins at step 702 with the Java tag handler calls SimpleTagBean.process with the appropriate tag element. At step 704, the SimpleTagBean hands the element off to its subclass's "overwritten" translateElement method. In the translateElement method, at step 706, the subclass looks at the element and its sub-elements and attributes to produce a text macro expansion of the node. The routine then continues at step 708 with the text expansion being returned to the SimpleTagBean.process method. At step 710, the XML is parsed backed into DOM. At step 712, the top node of the new document object replaces the element that was passed in from the previous document. In particular, in step 712, the top node of the new DOM replaces the element was passed into translateElement(). This completes the processing.

Text In, Text Out Tagbean

Figure 8 illustrates a Text in, Text out tagbean that may be used to isolate the developer from the DOM API. This is especially useful if the element contains only simple information or does simple query string

replacement. A representative class is as follows:

public abstract class TextTagBean extends SimpleTagBean

{

public abstract String

translateText(String text);

public final String

translateElement(Element element);

public final void

process(Element element);

}

TextTagBean extends the SimpleTagBean functionality. In particular, the TextTagBean extends the SimpleTagBean class and implements the translateElement function to inherit the String V DOM output functionality. Instead of the developer writing translateElement, however, he or she now writes translateText.

Referring now to Figure 8, the routine begins at step 802 with the Java custom DOM tag handler handing the SimpleTagBean.process the appropriate element. At step 804, the routine hands the element off to the "overwritten" translateElement method. At step 806, the translateElement method converts the DOM directly into its corresponding XML. In particular, the TextTagBean.translateElement() takes the element and flattens it into XML without interpreting any of the XML. The routine then continues at step 808, with the XML then being passed to the translateText method of the subclass. At step 810, the translateText method reads the string and processes it to return a new XML string. In particular, translateText looks at the XML string and manipulates it to produce another text representation of it and returns this representation to TextTagBean.translateElement(). At step 812, the new XML string is returned to the TextTagBean.translateElement, which returns the string to SimpleTagBean.process. SimpleTagBean.process finishes the processing at step 814, by turning the string into DOM and, at step 816, by replacing the previous element with the root of the new document. Thus, in step 816, the top node of the new DOM replaces the element that was passed into translateElement(). This completes the processing.

### Multiple Scripting Language Blocks

Another tagbean is illustrated in Figure 9. This routine, called `jsp:block`, enables page developers to use multiple scripting languages in the same page. As will be seen, this enables people with different skill sets to add value to the same page. It also enables the developer to chose another language that might be more suitable for a specific job.

The routine begins at step 902 with each `jsp:block` handed off to the `JSPBlockTagBean`. At step 904, the `JSPBlockTagBean` chooses the appropriate `BlockTagBean` according to the language attribute of the `jsp:block` element. At step 906, the language-specific `BlockTagBean` creates a `methodDefinition` element which, at step 908, is then filled with code to set up an appropriate runtime environment for the target language. At step 910, the `methodDefinition` element is inserted as a child of the root element in the document. The routine then continues at step 912 to create a `methodCall` element to replace the original `jsp:block` element.

### DOM Tree Processing

Figure 10 illustrates a preferred routine for collapsing the DOM tree into the fewest possible `methodCalls`. The routine begins at step 1002 to test whether there are any unprocessed `methodCalls` in the document. If not, the routine is done. If, however, the outcome of the test at step 1002 is positive, the routine continues at step 1004 by setting a variable `mc` equal to the right-most unprocessed leaf node that is a method call. At step 1006, the routine sets a variable `collapse` equal to an attribute `mc.getAttribute(collapse)`. At step 1008, the `collapse` attribute is checked. If this attribute is not true, control returns to step 1002. If the outcome of the test at step 1008 is positive, then the contents of the corresponding `methodDefinition` are expanded in place, and the `methodDefinition` and `methodCalls` are removed from the tree. In particular, the routine continues at step 1010 by setting a variable `md` equal to the `methodDefinition` for the `methodCall`. At step 1012, a test is run to determine whether any child nodes exist in the `methodDefinition` element. If not, the routine branches to step 1014 to remove `mc` from the document, and control returns to step 1002. If, however, the outcome of the test at step 1012 is positive, the routine continues at step 1016 to let `c` equal the last child node in the `methodDefinition`. At step 1018, `c` is removed from the `methodDefinition`. The routine then continues at step 1020 to insert `c` before `mc` in the document. Control then returns back to step 1012. This completes the processing.

For optimization purposes, it is desired to verify context between multiple related XML tags in a DOM. One or more of these related XML tags are custom tags within the context of the inventive framework. By way of brief background, when processing a single custom tag element, that element may need access to all other related tags, processed and unprocessed, within the DOM. Unfortunately, however, there may be other unprocessed custom tags in the DOM that, when processed, would result in one or more related tags the current element is interested in. One solution to this problem is to pass some state information from the current element through the page handling engine. A preferred technique, however, is to use the DOM itself to indicate state.

#### Clean-up Processing

Figure 11 is a flowchart illustrating this clean-up processing. The routine begins at step 1102 during the processing of the DOM tree with a current element being processed replacing itself with a placeholder element. The placeholder element includes attributes indicating its state. At step 1104, a test is performed to determine if a clean-up element already exists for the element being processed. If not, the current element then creates a clean-up element at step 1106. At step 1108, this clean-up element is added to the DOM in a position where it will be processed after all elements related to the current element have been processed. Thus, for example, the clean-up element is added to the DOM as a child node to the root position. If the outcome of the test at step 1104 indicates that such a clean-up element already exists, the current element need not create another clean-up element; rather, the current element need only move the existing clean-up element later in the DOM to ensure it is processed after any other related elements might be processed. This is step 1110. When the processing routine finally encounters the clean-up element, as indicated by a positive outcome of the test at step 1112, this element scans the entire DOM for all the related tags (now placeholders) of interest. This is step 1114. At step 1116, the clean-up element loads the state information from each and, at step 1118, processes them accordingly. When complete, at step 1120, the clean-up element removes itself from the DOM. In this way, the technique shifts processing from each individual element to a single, last-processed element.

Thus, in the preferred embodiment, a two-pass solution is implemented. In the first pass, simple translation is performed on the tag, creating new tag place holders to be handled by a clean-up phase. For example, assume the DOM includes the following tags: system:macrol,

system:macro2, and system:macro3. It is also assumed that each relies on specific information from other tags but not all the information is available until all of them have been touched once. On the first pass, system:macro1 expands to \_system\_macro1 and performs all the metadata expansion it can perform at this time to assist the clean-up node. At this time, it also inserts a system:cleanup in the tree as the last child of jsp:root (assuming it is not already there).

The second pass is triggered when the clean-up node is hit. For proper processing, it should check to make sure the first pass has completed (no system:macro1 or macro2 or macro3 tags in the tree). If other clean-up nodes exist in the tree, it should remove itself from the tree and let the other nodes handle the clean-up later. Once the clean-up node has determined that the tree is in the correct state, it goes through all the artifacts left by the first process and expands them with all the context available.

#### Tagbean Code Reduction

Another optimization reduces the amount of code in the tagbeans. By way of background, if a developer expands everything necessary to perform a function of a tag, that process may produce large amounts of code. In particular, the writing of custom tagbeans may result in a large amount of Java code being generated into the resulting servlet. Because this code may be largely common across servlets generated from the same tagbean (variable names might change, but little else), the functionality is delegated to outside code as much as possible. Preferably, the code is factored into a separate Java bean, and the most convenient place to delegate is the very tagbean generating the code. Thus, the tagbean need only generate enough Java code for the servlet to call out to the separate bean. This dramatically reduces the code in the tag bean handler.

As a result, this optimization improves maintainability and greatly simplifies debugging. In addition, because the code is not expanded, the function is hidden from anyone who has access to the generated servlet code. In addition, as a separate Java bean, developers are encouraged to put more error-handling code in the system that may not get put in otherwise. It also further stabilizes the system.

Thus, in a preferred embodiment, instead of doing inline expansion of code, the developer may take runtime values of attributes and sub-elements and generate code to make them parameters of a method on the very same bean



that can be called at runtime to do the real work. Thus, at translation time, a custom tag in the DOM tree is replaced, e.g., with a script that results in a line of code in a generated servlet. In that way, when the servlet is then executed at request time, the line of code invokes a method in a custom tagbean to perform a given function.

A more detailed example of this optimization technique is set forth later in this disclosure.

#### Examples

As has been previously described, the flowchart of Figure 2 illustrates the basic translation functionality of the present invention. An example of this operation is now provided. In the following example, mixedLanguages.xsp is a flat input file, mixedLanguagesDOM1.txt is a representation of the DOM after the input file has been parsed and some metadata has been added to the DOM, mixedLanguagesDOM2.txt is a representation of the DOM after the custom tags in the input file have been processed (in this case, the <block> tag is a custom tag, with the inner tag processed before the outer tag, with the resulting DOM then ready to be walked by the servlet generator routine), and mixedLanguagesServlet.java is the servlet generated by walking the DOM that complies with the JSP 1.0 specification.

mixedLanguages.xsp

```
<?xml version="1.0"?>
```

```
<jsp:root>
```

```
  <jsp:block language="java">
```

```
    <jsp:scriptlet>
```

```
      String user = request.getParameter("user");
```

```
      if (user == null) {
```

```
        </jsp:scriptlet>
```

```
        <b>No one is logged in.</b>
```

```
        <jsp:block language="javascript">
```

```
          <jsp:scriptlet>
```

```
            var int x = 0;
```

```
            x = x + 1;
```

```
          </jsp:scriptlet>
```

```
        </jsp:block>
```

```
      <jsp:scriptlet>
```

```
    }
```

```
    else {
```

```
  </jsp:scriptlet>
```

```

        <b>Welcome:
        <jsp:scriptlet>
        out.println(user);
        </jsp:scriptlet>
5         </b>
        <jsp:scriptlet>
        }
        </jsp:scriptlet>
        </jsp:block>
10    </jsp:root>

mixedLanguagesDOM1.txt
<jsp:root servletPath="c:\top\xsp\demo\test\mixedLanguagesServlet.java"
servletPackageName="xsp.test.scripting"
15    servletClassName="mixedLanguagesServlet">
        <jsp:methodDefinition name="_jspService">
            <jsp:block language="java">
                <jsp:block language="java">
                    <jsp:scriptlet>
20                        String user = request.getParameter("user");
                        if (user == null) {
                            <b>
                                No one is logged in.
                                <jsp:block language="javascript">
25                                    <jsp:scriptlet>
                                        var int x = 0;
                                        x = x + 1;
                                    </jsp:scriptlet>
                                }
30                                else {
                                    <b>
                                        Welcome:
                                        <jsp:scriptlet>
                                            out.println(user);
35                                        <jsp:scriptlet>
                                            }
                                }
        }
    </jsp:methodDefinition>
mixedLanguagesDOM2.txt
<jsp:root servletPath="c:\top\xsp\demo\test\mixedLanguagesServlet.java"
servletPackageName="xsp.test.scripting"
40    servletClassName="mixedLanguagesServlet">
        <jsp:methodDefinition name="javascriptBlock1">

```

```

<jsp:scriptlet>
    BSFManager bsfManager = new BSFManager();
    BSFEnvironment bsfEnvironment = new BSFEnvironment();
    bsfEnvironment.tempDir = "c:\\top\\";
5    bsfEnvironment.classPath =
    "c:\\top\\;c:\\prog\\jdk118\\lib\\classes.zip;c:\\top;c:\\prog\\xml4j\\xml4
    j_1_1_16.jar;c:\\prog\\lotusxsl_0_17_0\\lotusxsl.jar;c:\\prog\\SQLLIB\\java
    \\db2java.zip;c:\\prog\\SQLLIB\\java\\runtime.zip;c:\\prog\\websphere\\apps
    erver\\lib\\ibmwebas.jar;c:\\prog\\websphere\\appserver\\lib\\jsdk.jar;c:\\
10    prog\\websphere\\appserver\\lib\\jst.jar;c:\\top\\bsf-1.0b6\\lib\\bsf.jar;c
    :\\top\\bsf-1.0b6\\lib\\js.jar;c:\\top\\bsf-1.0b6\\lib\\NetRexxC.zip;c:\\pr
    og\\websphere\\appserver\\lib\\x509v1.jar;.;c:\\prog\\websphere\\appserver\\
    lib\\ejs.jar;c:\\;c:\\prog\\websphere\\appserver\\properties\\ejs;c:\\prog
    \\jdk116\\bin\\..\\classes;c:\\prog\\jdk116\\bin\\..\\lib\\classes.zip;c:\\
15    prog\\jdk116\\bin\\..\\lib\\classes.jar;c:\\prog\\jdk116\\bin\\..\\lib\\rt.
    jar;c:\\prog\\jdk116\\bin\\..\\lib\\i18n.jar";
    bsfEnvironment.classLoader = this.getClass().getClassLoader();
    bsfManager.setBSFEnvironment(bsfEnvironment);
    BSFEngine javascriptInterpreter =
20    bsfManager.loadScriptingEngine("javascript");
    javascriptInterpreter.setDebug(true);
    bsfManager.registerBean("request", request);
    bsfManager.registerBean("response", response);
    bsfManager.registerBean("session", session);
25    bsfManager.registerBean("out", out);
    bsfManager.registerBean("pageContext", pageContext);
    bsfManager.registerBean("page", this);
    try {
        javascriptInterpreter.eval("var request =
30    bsf.lookupBean(\"request\");\nvar response =
    bsf.lookupBean(\"response\");\nvar session =
    bsf.lookupBean(\"session\");\nvar out = bsf.lookupBean(\"out\");\nvar
    pageContext = bsf.lookupBean(\"pageContext\");\nvar page =
    bsf.lookupBean(\"page\");\n\n        var int x = 0;\n            x = x + 1;\n
35    ");
    } catch (BSFException e) {
        Throwable realException = e.getTargetException();
        while (realException instanceof BSFException) {
            realException = ((BSFException)
40    realException).getTargetException();

```

```

        while (realException instanceof
java.lang.reflect.InvocationTargetException) {
            realException =
((java.lang.reflect.InvocationTargetException)
5 realException).getTargetException();
        }
    }
    realException.printStackTrace();
    throw new ServletException(realException.getMessage());
10
    }
    bsfManager.unregisterBean("request");
    bsfManager.unregisterBean("response");
    bsfManager.unregisterBean("session");
    bsfManager.unregisterBean("out");
    bsfManager.unregisterBean("config");
15 bsfManager.unregisterBean("pageContext");
    bsfManager.unregisterBean("page");
    <jsp:methodDefinition name="_jspService">
        <jsp:scriptlet>
20     String user = request.getParameter("user");
        if (user == null) {
            <b>
                No one is logged in.
            <jsp:methodCall name="javascriptBlock1">
25 <jsp:scriptlet>
                }
                else {
                    <b>
                        Welcome:
30 <jsp:scriptlet>
                            out.println(user);
                        <jsp:scriptlet>
                            }
mixedLanguagesServlet.java
35 package xsp.test.scripting;

import org.w3c.dom.*;
import java.beans.*;
import com.lotus.xml.xml4j2tx.*;
40 import java.io.*;
import com.ibm.bsf.*;

```

```

import java.util.*;
import com.sun.server.http.*;
import javax.servlet.jsp.*;
import com.lotus.xsl.*;
5   import javax.servlet.*;
import xsp.*;
import com.ibm.servlet.pagecompile.*;
import com.ibm.xml.parser.*;
import java.net.*;
10  import com.sun.server.util.*;
import java.lang.*;
import javax.servlet.http.*;
import com.ibm.servlet.engine.*;

15  public class mixedLanguagesServlet
    extends xsp.ContractServlet
    {
        public void
        _jspService(HttpServletRequest req,
20          HttpServletResponse res)
            throws ServletException, IOException
        {
            // Cast to HttpService objects for setAttribute/callPage
            HttpServiceRequest request = (HttpServiceRequest) req;
            HttpServiceResponse response =
25          new PCHttpServletResponseProxy((SEHttpServiceResponse) res);
            JspWriter out = null;

            // Create the JspFactory and obtain the PageContext
30          JspFactory factory = JspFactory.getDefaultFactory();
            PageContext pageContext =
                factory.getPageContext(this, // JSP page
                                     request, // Servlet request
                                     response, // Servlet response
                                     null, // Error page URL
                                     true, // Servlet session
                                     0, // JSP buffer size
                                     true); // JSP autoflush

35

            try {
40                // Initialize all the implicit variables

```

```

HttpSession session = request.getSession(true);
out = pageContext.getOut();
Object page = this;
response.setContentType("text/html;charset=ISO-8859-1");

5
    // Now generate fixed template and script code

    String user = request.getParameter("user");
    if (user == null) {

10
        out.print("<b>");
        out.println();
        out.println("No one is logged in.");
        out.println("</b>");

15
        javascriptBlock1(request,
                           response,
                           session,
                           out,
                           pageContext,
20
                           page);
    }
    else {

        out.print("<b>");
25
        out.println();
        out.println("Welcome:");
        out.println(user);

        out.println("</b>");
30
    }

    } finally {
        out.close();
        ((PCHttpServletResponseProxy) response).writeOutResponse();
35
        factory.releasePageContext(pageContext);
    }
}

public void
40
javascriptBlock1(HttpServiceRequest request,
                  HttpServiceResponse response,

```

```

        HttpSession session,
        JspWriter out,
        PageContext pageContext,
        Object page)
5      throws ServletException, IOException
    {
        BSFManager bsfManager = new BSFManager();
        BSFEnvironment bsfEnvironment = new BSFEnvironment();
        bsfEnvironment.tempDir = "c:\\top\\";
10      bsfEnvironment.classPath =
        "c:\\top\\;c:\\prog\\jdk118\\lib\\classes.zip;c:\\top;c:\\prog\\xml4j\\xml4
        j_1_1_16.jar;c:\\prog\\lotusxsl_0_17_0\\lotusxsl.jar;c:\\prog\\SQLLIB\\java
        \\db2java.zip;c:\\prog\\SQLLIB\\java\\runtime.zip;c:\\prog\\websphere\\apps
        erver\\lib\\ibmwebas.jar;c:\\prog\\websphere\\appserver\\lib\\jsdk.jar;c:\\
15      prog\\websphere\\appserver\\lib\\jst.jar;c:\\top\\bsf-1.0b6\\lib\\bsf.jar;c
        :\\top\\bsf-1.0b6\\lib\\js.jar;c:\\top\\bsf-1.0b6\\lib\\NetRexxC.zip;c:\\pr
        og\\websphere\\appserver\\lib\\x509v1.jar;.;c:\\prog\\websphere\\appserver\\
        lib\\ejs.jar;c:\\;c:\\prog\\websphere\\appserver\\properties\\ejs;c:\\prog
        \\jdk116\\bin\\..\\classes;c:\\prog\\jdk116\\bin\\..\\lib\\classes.zip;c:\\
20      prog\\jdk116\\bin\\..\\lib\\classes.jar;c:\\prog\\jdk116\\bin\\..\\lib\\rt.
        jar;c:\\prog\\jdk116\\bin\\..\\lib\\i18n.jar";
        bsfEnvironment.classLoader = this.getClass().getClassLoader();
        bsfManager.setBSFEnvironment(bsfEnvironment);
        BSFEngine javascriptInterpreter =
25      bsfManager.loadScriptingEngine("javascript");
        javascriptInterpreter.setDebug(true);
        bsfManager.registerBean("request", request);
        bsfManager.registerBean("response", response);
        bsfManager.registerBean("session", session);
30      bsfManager.registerBean("out", out);
        bsfManager.registerBean("pageContext", pageContext);
        bsfManager.registerBean("page", this);
        try {
            javascriptInterpreter.eval("var request =
35      bsf.lookupBean(\"request\");\nvar response =
        bsf.lookupBean(\"response\");\nvar session =
        bsf.lookupBean(\"session\");\nvar out = bsf.lookupBean(\"out\");\nvar
        pageContext = bsf.lookupBean(\"pageContext\");\nvar page =
        bsf.lookupBean(\"page\");\n\n          var int x = 0;\n          x = x + 1;\n
40      ");
        } catch (BSFException e) {

```

```

        Throwable realException = e.getTargetException();
        while (realException instanceof BSFException) {
            realException = ((BSFException)
realException).getTargetException();
5           while (realException instanceof
java.lang.reflect.InvocationTargetException) {
                realException =
((java.lang.reflect.InvocationTargetException)
realException).getTargetException();
10            }
        }
        realException.printStackTrace();
        throw new ServletException(realException.getMessage());
    }
15    bsfManager.unregisterBean("request");
        bsfManager.unregisterBean("response");
        bsfManager.unregisterBean("session");
        bsfManager.unregisterBean("out");
        bsfManager.unregisterBean("config");
20    bsfManager.unregisterBean("pageContext");
        bsfManager.unregisterBean("page");
    }
}

```

25       The following illustrates more generally how an input file is translated into a DOM data structure. In particular, for a given input file:

```

<a>
    <b>
30        <c/>
        <d/>
    </b>
    <e>
        <f/>
35        <g/>
        <h/>
    </e>
</a>,

```

40       the DOM data structure would look as follows:



```

a
|--b
|  |--c
|  |--d
5 |
|--e
   |--f
   |  |--g
   |--h

```

Thus, in this example, node a is a parent node that has child nodes b and e. Node b has child nodes c and d, and node e has child nodes f and h. Node f has child node g. In the preferred embodiment, the order of node execution would then be as follows: c, d, b, g, f, h, e and a. The value of executing the nodes in an inside-out fashion is that the innermost tagbean can replace itself with a JSP syntax element that is well known to an outer tagbean so that the outer tagbean knows how to process the internal element.

For example, in the case of the multi-language support, like:

```

<block language="java">
  <jsp:scriptlet>
    javaExpression;
25   javaExpression2;
  </jsp:scriptlet>
  <block language="javascript">
    <jsp:scriptlet>
      javascriptExpression;
30     javascriptExpression2;
    </jsp:scriptlet>
  </block>
</block>

```

The block tag is a custom tag. When this tag executes, it transforms everything inside it into Java code. The embodiment is able to transform the contained custom tag because the innermost custom tag preferably is handled first, and such processing leaves behind a well known tag that the outer most custom tag handler knows how to transform.

The following code illustrates how scripting language blocks may be used to support multiple scripting languages in a single web page. As described above, nesting of different scripting languages is supporting by marking where one section, or "block", of code begins and where it ends.

For example, the following snippet has JavaScript code nested within REXX code nested within Java code:

```

5  if (true)  {
        say I am true
        if also Tue then do
10         var i = 5;
        end
        System.out.println(bean.getProperty());
    }

```

If this code were to appear in a web page, the blocks of code may be marked as follows:

```

15  <BLOCK language="java">
    if (true)  {
        <BLOCK language="netrexx">
            say I am true
20         if also True then do
                <BLOCK language="javascript">
                    var i = 5;
                    </BLOCK>
            end
25         </BLOCK>
            System.out.println(bean.getProperty());
        }
    </BLOCK>

```

In the above example, it can be seen that "end" is associated with "if alsoTrue then do" and not, for example, with "var i =5." This enables the code to correctly process all the languages at runtime. In the above example, it should be noted that the blocks are nested. This is not a limitation. Indeed, there is no reason they cannot be peers, as below:

```

35  <BLOCK language="java">
    // a little Java code here
    </BLOCK>
    <BLOCK language="javascript">
    /* some JavaScript code here */
40  </BLOCK>.

```

As described, the implementation compiles a web page into a XML (eXtensible Markup Language) DOM (Document Object Model), and from there, into a Java servlet. In the DOM stage, the routine looks for BLOCK nodes. When encountering one, the routine creates a new node representing a Java method definition as a child of the root element, and replaces the BLOCK node with a node representing a Java method call to the new method definition. The block's child nodes are then moved under the method definition. Java servlet code is then generated under the method definition to pass the script code contained in the block to an appropriate interpreter for the scripting language specified by the block's "language" attribute.

The same operation is done for nested blocks. The innermost block is turned into a method definition and replaced by the method call node. When the next outer block is processed into its method definition, the block must turn any method call nodes among its children into valid method calls into the servlet written in the outer block's language. In the nested example above, the resulting Java servlet might then contain code as follows:

```
protected void
javaBlock0(args)
{
    if (true) {
        netrexxBlock0(args);
        System.out.println(bean.getProperty());
    }
}
protected void
javascriptBlock0(args)
{
    javascriptInterpreter.process("var i = 5;");
}
protected void
netrexxBlock0(args)
{
    netrexxInterpreter.process("say I am true \n if alsoTrue then do \n
thisServlet.javascriptBlock0(args)\n end");
}
```

The bolded text above represents the method call node transformed into a valid method call in the particular scripting language. Because in the

preferred embodiment the runtime is written in Java, a special interpreter is not required to handle the javaBlock0 script code.

The following illustrates how context between multiple related XML tags is verified. This example starts with a sample input XML chunk and ends with a code chunk for use in the final servlet:

(1) xml

```
<trace:sink file="/myTrace.out">
  <trace:output>foo + bar</trace:output>
</trace:sink>
```

(2) trace:output is handled by TagBean

- creates a marker with all currently known state
- creates a trace:cleanup-markers tag which will signal the 2nd pass

```
<trace:cleanup-markers/>
<trace:sink file="/myTrace.out">
  <_trace_output_marker>foo + bar</_trace_output_marker>
</trace:sink>
```

(3) trace:sink is handled

- produces scriptlets to handle body of the work
- adds metadata to \_trace\_output\_marker

```
<trace:cleanup-markers/>
<jsp:scriptlet>
```

```
  try
```

```
    FileWriter fileWriter = new FileWriter("/myTrace.out");
    PrintWriter printWriter = new PrintWriter(fileWriter);
```

```
</jsp:scriptlet>
```

```
<_trace_output_marker output="printWriter">foo +
bar</_trace_output_marker>
```

```
<jsp:scriptlet>
```

```
  } finally {
```

```
    printWriter.flush();
```

```
    fileWriter.flush();
```

```
    printWriter.close();
```

```
    fileWriter.close();
```

```
  }
```

```
</jsp:scriptlet>
```

(4) trace:cleanup-markers is handled

- replaces `_trace_output_marker` with a `jsp:scriptlet`

```
<jsp:scriptlet>
    try
```

```
5         FileWriter fileWriter = new FileWriter("/myTrace.out");
           PrintWriter printWriter = new PrintWriter(fileWriter);
</jsp:scriptlet>
<jsp:scriptlet>
    printWriter.println(foo + bar);
10 </jsp:scriptlet>
<jsp:scriptlet>
    } finally {
        printWriter.flush();
        fileWriter.flush();
15        printWriter.close();
        fileWriter.close();
    }
</jsp:scriptlet>
```

20 (5) final translation step of `jsp:scriptlet` to Java code

```
    try
```

```
        FileWriter fileWriter = new FileWriter("/myTrace.out");
        PrintWriter printWriter = new PrintWriter(fileWriter);
25        printWriter.println(foo + bar);
    } finally {
        printWriter.flush();
        fileWriter.flush();
        printWriter.close();
30        fileWriter.close();
    }
```

As also noted above, the present embodiment provides a technique for reducing the amount of code in the tagbeans. An example of this optimization technique is now provided.

35

The following `ServletTagBean.j` is the original code file:

```
package xsp.was;
```

```
import xsp.*;
40 import java.util.*;
import org.w3c.dom.*;
```

```
import javax.servlet.jsp.*;
```

```
public class ServletTagBean extends SimpleTagBean
```

```
{
```

```
    protected String name = null;  
    protected String code = null;  
    protected String codebase = null;
```

```
    public void  
    setName(String name)  
    {  
        this.name = name;  
    }
```

```
    public void  
    setCode(String code)  
    {  
        this.code = code;  
    }
```

```
    public void  
    setCodebase(String codebase)  
    {  
        this.codebase = codebase;  
    }
```

```
    public String  
    translateElement(Element element)  
    {  
        Hashtable initParams = parseInitParams(element);
```

```
        // For each param sub element, add the name/value to a map for  
        later
```

```
        Hashtable paramMap = Utility.parseParams(element);
```

```

// The name or code parameter must be set.
if (name == null && code == null) {
    // Error!!!
    System.out.println("Error: name and code can not be null the same
5    time");
    return null;
}

StringBuffer buff = new StringBuffer();
10    buff.append("\n")
        .append("<")
        .append(ScriptletTag)
        .append(">\n\n")
        .append("try {\n")
15    .append("    String _code = null;\n");

    if (name == null) {
        buff.append("    String _name = null;\n");
    }
20    else {
        buff.append("    String _name = \"")
            .append(name)
            .append("\";\n");
    }

25    if (code != null) {
        buff.append("    _code = \"")
            .append(code)
            .append("\";\n\n");
30    }

    buff.append("\n    if (_name == null || _name.equals(\"\")) {\n")
        .append("        _name = _code;\n")
        .append("    }\n\n")
35    .append("    Servlet _s = \n")
        .append("        getServletConfig().getServletContext().")
        .append("getServlet(_name);\n")
        .append("    if (_s == null) {\n")
        .append("        Properties _init = new Properties();\n")
40    .append("        _init.put(\"name\", \"")
        .append(name)

```

10  
15  
20  
25  
30  
35  
40



}

40

[illegible]

```

        }
    }
    return initParams;
}

```

5

```

}

```

The following class, ServletTagBean.java, is the recoded class using the delegation model.

```

package xsp.was;

```

10

```

import xsp.*;
import java.io.*;
import java.util.*;
import org.w3c.dom.*;
import javax.servlet.*;
import javax.servlet.http.*;
import javax.servlet.jsp.*;
import com.sun.server.http.pagecompile.*;

```

20

```

public class ServletTagBean extends SimpleTagBean
{

```

```

    protected static int count = 0;

```

25

```

    public String
    translateElement(Element element)
    {

```

30

```

        Properties initParameters = parseInitParams(element);
        Hashtable runtimeParameters = Utility.parseParams(element);

```

```

        String name = (String) initParameters.get("name");
        String code = (String) initParameters.get("code");
        String codebase = (String) initParameters.get("codebase");

```

35

```

        // The name or code parameter must be set.
        if ((name == null) &&
            (code == null)) {

```

40

```

            System.out.println("Error: name and code can not be null the
            same time");
            return null;

```

```

    }
    int currentCount = ++count;

    String initParametersName =
5        "_xsp_servletTagBean_initParameters" + currentCount;

    String runtimeParametersName =
        "_xsp_servletTagBean_runtimeParameters" + currentCount;

10    String output =
        INDENT2 + "<jsp:scriptlet>\n" +
        INDENT2 + "Properties " + initParametersName + " = " +
        " new Properties();\n" +
        INDENT2 + "Properties " + runtimeParametersName +
15        " = new Properties();\n";

    Enumeration enumeration = initParameters.keys();
    while (enumeration.hasMoreElements()) {
        String key = (String) enumeration.nextElement();
20        String value = (String) initParameters.get(key);
        output +=
            INDENT2 + initParametersName + ".put(" +
            stringify(key) + ", " +
            stringify(value) + ");";
25    }

    enumeration = runtimeParameters.keys();
    while (enumeration.hasMoreElements()) {
        String key = (String) enumeration.nextElement();
        String value = (String) runtimeParameters.get(key);
30        output +=
            INDENT2 + runtimeParametersName + ".put(" +
            stringify(key) + ", " +
            stringify(value) + ");";
    }
35    output +=
        INDENT2 + "xsp.was.ServletTagBean.runServlet(this, \n" +
        INDENT3 + "request,\n" +
        INDENT3 + "response,\n" +
        INDENT3 + initParametersName + ",\n" +
40        INDENT3 + runtimeParametersName + ");";

```

```

        output +=
            INDENT2 + "</jsp:scriptlet>\n";

        return output;
5      }

    protected static final String
    normalize(String input)
10    {
        if (input == null) {
            return null;
        }
        input = input.trim();
        if (input.equals("")) {
15            return null;
        }
        return input;
    }
20

    protected static final String
    stringify(String input)
    {
25        if (input == null) {
            return "null";
        }
        return "\"" + input + "\"";
    }
30

    public static void
    runServlet(Servlet containingServlet,
               HttpServletRequest request,
35               HttpServletResponse response,
               Properties initParameters,
               Properties runtimeParameters)
        throws ServletException, IOException
    {
40        String name = normalize((String) initParameters.get("name"));
        String code = normalize((String) initParameters.get("code"));

```

```

        String codebase = normalize((String)
initParameters.get("codebase"));

        if ((name == null) &&
5           (code == null)) {
            throw new IllegalStateException("name or code must be
non-null");
        }
        if (name == null) {
10           name = code;
        }
        initParameters.put("name", name);
        if (code != null) {
            initParameters.put("code", code);
15        }
        Servlet servlet = ServletUtil.loadServlet(containingServlet,
                                                    name,
                                                    code,
                                                    codebase,
20           initParameters);

        if (!runtimeParameters.isEmpty()) {
            request = new ParamsHttpRequest(request,
runtimeParameters);
25        }
        ServletUtil.callServlet(servlet, name, request, response);
    }

30    public Properties
    parseInitParams(Element element)
    {
        Properties initParams = new Properties();

35        NamedNodeMap namedNodeMap = element.getAttributes();
        int attributeLength = namedNodeMap.getLength();

        Node attributeNode = null;
        String nodeName = null;
40        String nodeValue = null;

```

```

    for (int i = 0; i < attributeLength; i++) {
        attributeNode = namedNodeMap.item(i);
        nodeName = attributeNode.getNodeName();
        nodeValue = attributeNode.getNodeValue();

5         initParams.put(normalize(nodeName),
                           normalize(nodeValue));
    }
    return initParams;
10 }
}

```

The developer need not write code generation code to produce code that will be robust for every possible input scenario. Instead, the developer need only write the code once, and the only code generation is used to delegate to the method that is written once.

So, to provide a generic example:

1. String output = "out.write(\"" + string + "\");";

becomes:

2. String output = "PrintTagBean.print(out, \"" + string + "\");";

The out.write() is moved into a method print() on PrintTagBean:

```

public static void
print(Writer out,
      String string)
25 {
    out.write(string);
}

```

As can be seen, in the first case, the code relies upon a variable 'out' that exists in the servlet. The write() method was called on 'out' passing it a string. Thus, to perform proper delegation, a method on PrintTagBean is created that takes 'out' and the 'string' and calls "out.write(string)".

Thus, at translation time, a custom tag in the DOM tree is replaced, e.g., with a script that results in a line of code in a generated servlet. In this way, when the servlet is then executed at request time, the line of code invokes a method in a custom tagbean to perform a given function.

If the code generated to handle runtime requests is longer than the code generated to pass the necessary variables to a method to be processed,

there are several benefits to this approach. First, writing code to generate code is a very tedious and error-prone task; thus, reducing this code even slightly reduces the numbers of errors drastically. Second, using this approach, all the code handling of a task is actually handled in a single method that can be carefully crafted to handle correct inputs to produce the right output. Because this code is in the tagbean, it can be compiled immediately and checked for language syntax errors. If, instead, the code is generated each time, it will not be compiled until an XSP is written to test the functionality. Moreover, with branching (if statements) in code generation, it may take several tests just to test the syntax of all the possible code generations. Further, if the developer needs to change the function and "optimization" has already taken place, then the developer need only update a single method. Otherwise, the developer must go through the process of updating all the code generating code. Because of this reduction in code and code complexity, the maintenance of the code will be much lower.

The present embodiment provides numerous other advantages over the prior art. In effect, the page handling mechanism combines the manipulation and template mechanism of XSLT with the scripting capabilities of the JSP/ASP model. In addition, the embodiment provides a framework for enabling any programming language to be plugged into that model. Further, given that most languages are easily defined in Java byte code, the invention is economical to implement in a runtime using, for example, a Java Virtual Machine.

The present embodiment uses custom DOM tags together with a framework and runtime that provides a powerful macro language to XML/JSP. The custom DOM tags allow a web page author the ability to define a simple markup language tag, e.g., <SHOPPING\_CART>, that, at page translation time, is converted into script code by a generic Java object or an XSL stylesheet. This script code is then compiled into Java code and then into a Java servlet, yielding excellent performance servicing a client's request. Because the custom tag replaces the script code in the authored page, the page is kept clean and easy to maintain. The script code is kept separate and, thus, need only be debugged once. Normal ASP development, on the contrary, would force this code to remain in the page, and it would have to be debugged after every modification.

The framework is quite advantageous in that it is built on top of XML. Moreover, one of ordinary skill will appreciate that the framework is defineable programmatically or with XSL. In addition, macros written



according to the embodiment can affect the output of an entire page and not just the content between a given pair of tags.

5 The embodiment also enables one or more web page authors to support multiple scripting languages in a single web page. Further, the context of multiple related XML tags in a DOM may be verified by using the DOM itself to indicate state information.

10 As noted above, the invention mechanism is preferably implemented in or as an adjunct to a web server. Thus, the invention does not require any modifications to conventional client hardware or software. Generalizing, the above-described functionality is implemented in software executable in a processor, namely, as a set of instructions (program code) in a code module resident in the random access memory of the computer. Until  
15 required by the computer, the set of instructions may be stored in another computer memory, for example, in a hard disk drive, or in a removable memory such as an optical disk (for eventual use in a CD ROM) or floppy disk (for eventual use in a floppy disk drive), or downloaded via the Internet or other computer network.

20 In addition, although the various methods described are conveniently implemented in a general purpose computer selectively activated or reconfigured by software, one of ordinary skill in the art would also recognize that such methods may be carried out in hardware, in firmware, or  
25 in more specialized apparatus constructed to perform the required method steps.

30 Further, as used herein, a Web "client" should be broadly construed to mean any computer or component thereof directly or indirectly connected or connectable in any known or later-developed manner to a computer network, such as the Internet. The term Web "server" should also be broadly construed to mean a computer, computer platform, an adjunct to a computer or platform, or any component thereof. Of course, a "client" should be broadly construed to mean one who requests or gets the file, and  
35 "server" is the entity which downloads the file.

CLAIMS

1. A method for serving a web page, comprising the steps of:  
processing a given file into XML compliant code;  
5 translating the XML compliant code into an object model  
representation having at least one custom tag;  
processing the object model representation to generate executable  
code; and  
invoking the executable code to generate the web page.  
10
2. The method claimed in Claim 1 wherein the step of processing the  
object model representation includes the steps of:  
parsing the object model representation to identify a custom tag; and  
upon identifying a custom tag, invoking a handler that converts the  
15 custom tag into a given representation.
3. The method claimed in Claim 2 wherein the given representation is  
script code.
- 20 4. The method claimed in Claim 2 wherein the handler is a stylesheet  
handler.
5. The method claimed in Claim 4 wherein the step of invoking the  
handler comprises:  
25 loading a stylesheet; and  
passing the stylesheet and the object model representation to a  
processor.
6. The method claimed in Claim 2 wherein the handler is a Java handler.  
30
7. The method claimed in Claim 6 wherein the step of invoking the  
handler comprises:  
loading a Java object;  
calling a process method on the Java object; and  
35 replacing the custom tag with the given representation.
8. The method claimed in Claim 1 further including the step of  
registering the custom tag together with data identifying a handler prior  
to processing the flat file.  
40

9. The method as described in Claim 1 wherein the executable code is a servlet.

10. The method claimed in Claim 1 wherein the object model representation is a tree data structure.

11. A method of serving a web page, comprising the steps of:  
registering a set of custom tags;  
upon a given occurrence, processing a flat file into XML compliant code;  
translating the XML compliant code into a document object model having a subset of the set of custom tags;  
processing the document object model to generate a servlet;  
compiling the servlet into executable code; and  
invoking the executable code to generate the web page.

12. The method claimed in Claim 11 wherein the given occurrence is a first access of the web page.

13. The method claimed in Claim 11 wherein the document object model is a tree structure.

14. The method claimed in Claim 13 wherein the step of processing the document object model includes the steps of:  
parsing the tree structure to identify each custom tag; and  
upon identifying each custom tag, invoking a handler that converts the custom tag into given script code.

15. The method claimed in Claim 14 wherein the handler applies a XSL stylesheet to generate the given script code.

16. The method claimed in Claim 14 wherein the handler executes a Java code object to generate the given script code.

17. A computer program product in a computer-readable medium for managing the serving of a web page from a server, comprising:  
means operative upon a given occurrence for processing a flat file into XML compliant code;  
means for translating the XML compliant code into a document object model having a set of custom tags; and

means for processing the document object model to generate servlet code that may be compiled and invoked to generate the web page.

18. The computer program product claimed in Claim 17 further including means for registering a superset of custom tags.

19. The computer program product claimed in Claim 17 wherein the means for processing comprises:

means for parsing the tree structure to identify each custom tag; and means responsive to identification of a custom tag for invoking a handler that converts the custom tag into given script code.

20. The computer program product claimed in Claim 19 wherein the handler applies a XSL stylesheet to generate the given script code.

21. The computer program product claimed in Claim 19 wherein the handler executes a Java object to generate the given script code.

22. A server, comprising:

a processor;  
an operating system;  
a server program;  
a registry of custom tags;  
means operative upon a given occurrence for processing a flat file into XML compliant code;  
means for translating the XML compliant code into a document object model having a set of custom tags;  
means for processing the document object model to generate servlet code;  
means for compiling and class loading the servlet code; and  
means for invoking the servlet code to generate the web page.

23. A web page, generated by:

processing a given file into XML compliant code;  
translating the XML compliant code into an object model representation having at least one custom tag;  
processing the object model representation to generate executable code; and  
invoking the executable code.



INVESTOR IN PEOPLE

Application No: GB 0022534.2  
Claims searched: 1-23

Examiner: Adam Tucker  
Date of search: 11 June 2001

## Patents Act 1977 Search Report under Section 17

### Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK Cl (Ed.S): G4A APL, AUSB

Int Cl (Ed.7): G06F 9/30, 9/44, 9/45, 17/21, 17/30

Other: Online: WPI, EPODOC, PAJ, COMPUTER, INSPEC, IEL and selected internet sites

### Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
X, P	WO00/45304 OBJECT DESIGN INC. see summary of the invention page 7 lines 3-19, page 12 lines 14-36, page 18 line 27-page 19 line 4 and Fig. 8	1, 2, 3, 6, 7, 9-14, 16-19, 21-23
Y, P	<a href="http://www.chesco.com/~randzman/CFDOCS/moredocs/adv_cf_devel.pdf">http://www.chesco.com/~randzman/CFDOCS/moredocs/adv_cf_devel.pdf</a> , Advanced ColdFusion Development, last modified 07/09/2000, pp246-247 and 249-250	1-7, 9, 10, 17, 19-21, 23
X, P	<a href="http://www.redbooks.ibm.com/pubs/pdfs/redbooks/sg245479.pdf">http://www.redbooks.ibm.com/pubs/pdfs/redbooks/sg245479.pdf</a> , The XML Files: Using XML and XSL with IBM Websphere 3.0, last modified 27/03/2000, pp 39-40, 65-66, 68-69 and 72-73	1-7, 9, 10, 17, 19-21, 23
X, Y	<a href="http://java.sun.com/products/jsp/techinfo.html">http://java.sun.com/products/jsp/techinfo.html</a> , JavaSever Pages Specification 1.0, last modified 27/09/1999, pp 26-27 and 46-47	X: 1-7, 9, 10, 17, 19-21, 23 Y: 1-7, 9, 10, 17, 19-21, 23
X	<a href="http://www.cs.nyu.edu/others/research/mu_spin/muspin99.pdf">http://www.cs.nyu.edu/others/research/mu_spin/muspin99.pdf</a> , MU-SPIN Ninth Annual Users Conference, The Next Generation Web Servers, Dr Kung, 27/09/1999, p20	1-7, 9, 10, 17, 19-21, 23

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.



INVESTOR IN PEOPLE

Application No: GB 0022534.2  
Claims searched: 1-23

Examiner: Adam Tucker  
Date of search: 11 June 2001

Category	Identity of document and relevant passage	Relevant to claims
X	<a href="http://zdnet.com/filters/printerfriendly/0,6061,409493-2,00.html">http://zdnet.com/filters/printerfriendly/0,6061,409493-2,00.html</a> , Lutris' server divides duties, Antone Gonsalves, 11/07/1999	1-3, 6, 7, 9, 10, 17, 19, 21, 23

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application